



Bearing Mexico, S.A.



E-PF-TRB-75MM Bearing 2D drawings and 3D CAD models

TIMKEN E-PF-TRB-75MM Flange Block Bearings

Bearing No. E-PF-TRB-75MM

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	12.277
EAN	0053893778785
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Metric
Long Description	4 Bolt Round Flange Block; 75MM Bore; 190MM Bolt Circle; 134.7MM Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Tapered Roller Bearing; 114.3MM Length Thru Bore; Relubricatable; Doub



Bearing Mexico, S.A.

Other Features	Double Row Wide Inner Race With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	E-PF-TRB-75MM
Weight / LBS	10
D	4.5 Inch 114.3 Millimeter
Cartridge Pilot Depth	2.438 Inch 61.925 Millimeter
Bolt Spacing	5.3 Inch 134.7 Millimeter
d	2.953 Inch 75 Millimeter
Cartridge Pilot Diameter	6.375 Inch 161.92 Millimeter
Nominal Bolt Circle Diameter Round	7.5 Inch 190 Millimeter
Shaft Size	2.953 in
Shaft Size Type	Metric
Weight	25 lb
UPC Code	053893778785
Nose Diameter	5.99 in
Nose Bore Diameter	4.7 in
Dimension B	4-1/2 in
Dimension H	8-3/4 in
Dimension A	3-11/16 in
Dimension N ₂	5.300 in
Dimension J	7-1/2 in
Dimension A ₃	1-1/2 in
Bolt Diameter	5/8 in
Dimension E	2 in



Bearing Mexico, S.A.

Dimension A ₁	3/4 in
Dimension D ¹	6-3/8 in
Dimension d ₁	4-23/32 in
Dimension A ₂	1-1/4 in
e	0.46
X (if F _a /F _r ≤ e)	0.87
Y (if F _a /F _r ≤ e)	1.87
X (if F _a /F _r > e)	0.7
Y (if F _a /F _r > e)	2.26
K Factor	1.30
C ₉₀ Dynamic Load Rating ²	12300 lb
C ₀ Static Load Rating	61200 lb
F _{a-max} Maximum Permissible Thrust Load ³	5181 lb
F _{r-max} Maximum Allowable Slip Fit Radial Load ⁴	10000 lb
Max. Speed ⁵	2060 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur